



### NOTES

- Usable storage capacity is based on 45° angle of repose.
- Normal discharge capacity is 6.5 units per hour.
- One unit is equal to 200 cubic feet or 5.664 cubic meters.
- Silo has negative slope.

Storage Capacity in Units				
Bin	Model	Usable	Level Full	“C” Dimension
A-13	40	29	32	59'
	30	23	26	49'
	20	16	19	39'
	10	10	13	29'
A-17	40	48	53	63'3"
	30	38	43	53'3"
	20	27	33	43'3"
	10	16	22	33'3"
A-19	40	60	67	65'1"
	30	47	54	55'1"
	20	33	41	45'1"
	10	19	28	35'1"
A-21	40	72	82	66'9"
	30	57	67	56'9"
	20	40	51	46'9"
	10	23	35	36'9"
A-24	40	100	116	70'1"
	30	78	96	60'1"
	20	56	74	50'1"
	10	32	51	40'1"
A-30	40	152	182	75'2"
	30	118	150	65'2"
	20	83	117	55'2"
	10	46	83	45'2"

Model	“A” Dimension	“B” Dimension
A-13	13'4"	16'7"
A-17	17'2"	20'5"
A-19	19'1"	22'4"
A-21	21'0"	24'3"
A-24	24'10"	28'1"
A-30	30'7"	33'10"